



E-mail: sales@amsilicones.co.uk

Web Page: www.SiliconeRubberExtrusions.co.uk

Technical Data Sheet: SAB PH8441

PRODUCT OVERVIEW

A self-adhesive backing tape for application to our Food Grade Sponge extrusion

The tape features a high temperature resistant acrylic tissue tape on a brown release liner

PRODUCT CONSTRUCTION

Liner: 80g Brown siliconized release paper

Carrier: 13G tissue

Adhesive: Acrylic based with 45gsm on both open and closed sides

Total thickness: 115 microns

PERFORMANCE PROPERTIES

Peel adhesion to steel (24-hour dwell) protected 650 N/M open 650 N/M

Shear adhesion to steel: protected 50 hours open 50 hours

Service temperature range: -10°C to 180°C

Recommended application temperature: 5°C to 60°C

Shelf life: Recommended 3 months from supply

FOOD CONTACT INFORMATION

Based on supplier information the raw materials used in producing the adhesive tape conform to the compositional requirements of F&DA 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the responsibility of the customer.

Figures given above are for guidance only and should not be used in preparing specifications.

E & O.E.

**Advanced Materials Limited, Unit 17, Arndale Road, Lineside Ind Est, Littlehampton, West Sussex BN17 7HD
Telephone 01903 713566**

Data Prepared 3Q2022